

ISOPEX ISAS (. 1943) OPR 412-133 TO MM ELROCLASSE & SS OFF. MADE IN TIRLY

ISOPEX





www.zetaesse.it



EuroPex + ZETACELL = IsoPex

PEXb - AL - PEXb multilayer pipe with reticulated polyethylene foam ZETACELL, to guarantee the best performance.

HIGH TEMPERATURE RESISTANCE

Since PE-X has a high heat limit, it lets IsoPex pipes work in excellent conditions both in heating and cooling systems without any problems due to heat excursions and temperature changes.

MECHANICAL RESISTANCE

Insulation material more compact and resistant.

REACTION TO FIRE

Euroclasse B s2 d0 secondo EN 13501-1 CE.

LONG-LIFE

The external LDPE film provides to the insulation greater strength and mechanical protection, which keeps its properties constant in time as a result. Heat conductivity λ 0/40°C = 0,0377/0,0435 W/m °C. Marking: ZETAESSE ISOPEX 16X2 L.10/91 DPR 412/93 10 mm EUROCLASSE B s2 d0 EN 13501-1 CE MADE IN ITALY.



Dimensions	Insulation thickness	Length
mm	mm	m
16X2 20X2 26X3 32X3	7/10 7/10 7/10 10/14	100 50 50 25

